

DEPARTMENT OF TRANSPORTATION
FEDERAL RAILROAD ADMINISTRATION
FALSE PROCEED SIGNAL REPORT

REPORT FOR (month/year)
 November 1995

DATE
 November 21, 1995

All railroads subject to Regulations of the Federal Railroad Administration shall submit a false proceed signal report, original only, to the Federal Railroad Administration within five days after a false proceed occurs. If no false proceed occurs during any calendar month, a report showing "No Failures" must be filed within ten days after the end of the month.

Copies of this form will be furnished upon request to the Department of Transportation, Federal Railroad Administration, Office of Safety, Washington, D.C. 20590.

REPORTING CARRIER (railroad & region or division)
 Union Pacific Railroad
 1416 Dodge Street
 Omaha, Nebraska
 Council Bluffs Service Unit

MAIL TO

Director of Railroad Safety
 Federal Railroad Administration
 City Center Square, Suite 1130
 1100 Main Street
 Kansas City, MO 64105-2112

REPORTING OFFICER (signature/title)

 Chief Engineer-Signals

The following abbreviations may be used in the report:

A failure should not be counted more than one time in items 1, 2, 3, and 4; the failure should be classified under the basic system or appliance of which it forms an essential part. E.g.; assume grounds range a block signal to indicate a false proceed causing corresponding indications of a cab signal system on each train approaching this point, such failures should be included in item 1, Block Systems.

A false proceed failure is a failure of a system, device or appliance to indicate or function as intended which results in less restriction than intended.

- A = Automatic
- AB = Automatic block
- ACS = Automatic Cab Signal
- APB = Absolute permissive block
- ATC = Automatic train control
- ATS = Automatic train stop
- CL = Color light
- CPL = Color position light
- E = Electric
- EM = Electromechanical
- EP = Electropneumatic
- FP = False proceed
- MB = Manual block
- M = Mechanical
- P = Pneumatic
- PL = Position light
- SA = Semiautomatic
- TC = Traffic Control

TYPE OF SYSTEM	DATE	LOCOMOTIVE NUMBER	DEVICE THAT FAILED	LOCATION(city and state)
1 BLOCK SYSTEMS <input type="checkbox"/> AB <input type="checkbox"/> APB <input checked="" type="checkbox"/> TC	11/9/95	UP2324	None	Marysville, Kansas
2 INTERLOCKING <input type="checkbox"/> AUTOMATIC <input type="checkbox"/> REMOTE <input type="checkbox"/> MANUAL				
3 AUTOMATIC SYSTEMS <input type="checkbox"/> ATS <input type="checkbox"/> ATC <input checked="" type="checkbox"/> ACS				
4 OTHER (Specify)				

NATURE AND CAUSE OF FAILURE/CORRECTIVE ACTION TAKEN

On November 8, 1995, at 11:15 (CST) on the Marysville Subdivision, westbound LNE75-08 flagged by red signal at Z150. The westbound train ahead of LNE75-08 was stopped by the Signal No. 153.7 with 2½ cars of the train east of the insulated joints. As LNE75-08 approached Signal No. 153.7, his cab signal upgraded from red to yellow.

An investigation revealed the current of the ACS east of the insulated joint at Signal No. 153.7 was 3 amps which allowed the current to pass under the stopped 2½ cars upgrading the ACS in LNE75-08.

The signal system was restored to proper operation, and all applicable tests were performed.

(If more space is required, continue on reverse)