

DEPARTMENT OF TRANSPORTATION
FEDERAL RAILROAD ADMINISTRATION
FALSE PROCEED SIGNAL REPORT

REPORT FOR (month/year)

September 1998

DATE

September 21, 1998

REPORTING CARRIER (railroad & region or division)

Union Pacific Railroad
 1416 Dodge Street
 Omaha, Nebraska
 Tucson Service Unit

REPORTING OFFICER (signature/title)

Chief Engineer-Signals

All railroads subject to Regulations of the Federal Railroad Administration shall submit a false proceed signal report, original only, to the Federal Railroad Administration within five days after a false proceed occurs. If no false proceed occurs during any calendar month, a report showing "No Failures" must be filed within ten days after the end of the month.

Copies of this form will be furnished upon request to the Department of Transportation, Federal Railroad Administration, Office of Safety, Washington, D.C. 20590.

MAIL TO

Director of Railroad Safety
Federal Railroad Administration
 City Center Square, Suite 1130
 1100 Main Street
 Kansas City, MO 64105-2112

FEDERAL RAILROAD ADMINISTRATION
 '98 SEP 23 A9:12

The following abbreviations may be used in the report:

A failure should not be counted more than one time in items 1, 2, 3, and 4; the failure should be classified under the basic system or appliance of which it forms an essential part. E.g.; assume grounds range a block signal to indicate a false proceed causing corresponding indications of a cab signal system on each train approaching this point, such failures should be included in item 1, Block Systems.

A false proceed failure is a failure of a system, device or appliance to indicate or function as intended which results in less restriction than intended.

- A = Automatic
- AB = Automatic block
- ACS = Automatic Cab Signal
- APB = Absolute permissive block
- ATC = Automatic train control
- ATS = Automatic train stop
- CL = Color light
- CPL = Color position light
- E = Electric
- EM = Electromechanical
- EP = Electropneumatic
- FP = False proceed
- MB = Manual block
- M = Mechanical
- P = Pneumatic
- PL = Position light
- SA = Semiautomatic
- TC = Traffic Control

TYPE OF SYSTEM	DATE	LOCOMOTIVE NUMBER	DEVICE THAT FAILED	LOCATION(city and state)
1 BLOCK SYSTEMS <input checked="" type="checkbox"/> AB <input type="checkbox"/> APB <input type="checkbox"/> TC	9/10/98	UP 5555	None	El Paso, TX
2 INTERLOCKING <input type="checkbox"/> AUTOMATIC <input type="checkbox"/> REMOTE <input type="checkbox"/> MANUAL				
3 AUTOMATIC SYSTEMS <input type="checkbox"/> ATS <input type="checkbox"/> ATC <input type="checkbox"/> ACS				
4 OTHER (Specify)				

NATURE AND CAUSE OF FAILURE/CORRECTIVE ACTION TAKEN

On September 10, 1998, at 17:55 MDT, on the Valentine Subdivision, at El Paso, TX, eastbound UP 5555, was lined from the House Track to the #2 Main Track, at Mile Pole 826.5, and observed the eastbound signal was green over red with the #3 crossover lined against them.

An investigation revealed the signal appeared to give a green indication due to the reflection of the sun on the lens.

A Phantom Screen was installed in the signal, and all applicable tests were performed.

(If more space is required, continue on reverse)